

Prewired Raised-Floor Box Assemblies

Provides **quick, simple, safe, cost-effective** installation of a wide variety of configurations.

Seamless interface with **EZ-Wiring**[®] system.

Features and Benefits:

- **ELECTEC EZ-Wiring**[®] components are UL Listed to UL 183 – Manufactured Wiring Systems (QQVX) and CSA Certified to CSA 22.2 No. 203-1 - Manufactured Wiring Systems.
- Constructed using **ULTRALX**[®] MC/AC90 cable (300lbs Tension), minimum 12AWG stranded conductors rated 600V 20A.
- Robust terminal design exceeds 470Amp for 4 seconds.
- **EZ-Wiring**[®] connectors are integrally moulded (fully encapsulated) utilizing high impact Halogen-free, Eco-Friendly, Low Smoke, UL94-V0 rated, Oxygen Index - 33 %, RoHS-compliant polymers for superior strength, reliability and safety.
- Dielectric Withstand 3000Vac.
- Mating connectors are self-latching and shrouded for added protection.
- Uniquely-keyed and colour-coded to clearly indicate ratings and provide safe, simple, error-free connectivity. Only connectors having identical colours can plug together properly.
- Suitable for use in environmental air handling spaces (plenums) per NEC 300-22(c) and CEC Part 1 12-010(3)
- Acceptable for interrupting current (make or break) under full load.
- Capping of unused connector openings is optional as **EZ-Wiring**[®] components have been evaluated to prevent inadvertent contact with live parts.
- Assemblies are prewired to plug-in connectors for quick, simple, safe, cost-effective installation.
- Attractive, durable design.
- Adjustable mounting to accommodate various floor thicknesses.
- An economical solution for virtually every application.
- Interfaces with **EZ-Wiring**[®] products



Ordering Information

Catalogue No.; **1H – VC – LNGO – B xxyyzz T F P II M G S DD C**

				B															
--	--	--	--	----------	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

VC	System		21 = 125/250V 15A, 22 = 125/250V 20A
LNGO	Application	3w	1110 = (L,N,G),
		4w	2110 = (2L,N,G), 1120 = (L,N,G,IG)
		5w	2210 = (2L,2N,G), 3110 = (3L,N,G)
		6w	3120 = (3L,N,G,IG), 2220 = (2L,2N,G,IG)
		7w	3310 = (3L,3N,G), 4210 = (4L,2N,G)
		8w	3320 = (3L,3N,G,IG), 4220 = (4L,2N,G,IG)
xxyyzz	Enclosure Dimensions	xx = Length in inches (00 = round), yy = Width in inches, zz = Height in inches	
T	Trim	C = Carpet, I = Tile	
F	Finish	A = Bushed Aluminum, B = Brass, G = Gray, I = Ivory, K = Black, N = Brown	
P	Supply End	D = Drop Cable, P = Plug, I = "T"/Cable, Z = Plug + Rec.	
II	Cable Length (in dm)	e.g. 40 = 4.0m, XX = not applicable	
M	Device Manufacturer	E = Eaton, G = Generic, H = Hubbell, L = Leviton, P = P&S	
G	Device Grade	C = Commercial, R = Residential (TR), S = Specification	
S	Device Style	A = snap-in, D = Decorator, R = Regular	
DD	Device Type	D = Duplex, R = Single receptacle, N = Comm./Data bracket, X = no device	
C	Colour	A = Almond, G = Gray, I = Ivory, K = Black, N = Brown, O = Orange, R = Red, U = Blue, W = White, X = n/a	

Adhere to all Code requirements and carefully follow installation instructions