

- BRASS BLADE
- BRASS TERMINAL
- MOULDED THERMOPLASTIC
- "ULTRALX" AC90 LS 600V 90°C (CSA 22.2 No. 51-95)
- SHROUD

WHERE "cc" REPRESENTS COLOUR CODE I.E. "BK" IS BLACK WHERE "d" REPRESENTS CERTIFIED WIRING MATERIAL I.E. "A" IS AC90 WHERE "III" REPRESENTS LENGTH CODE I.E. "040" IS 04.0 METERS

WHERE "w" REPRESENTS NUMBER OF WIRES FROM 3 TO 7

SYSTEM IS RATED FOR CONNECTION TO A GROUNDED 277/480V OR 347/600V BRANCH CIRCUIT. MANUFACTURED WIRING SYSTEM UTILIZING 12 AWG APPROVED ULTRALX CABLE. INSTALLATION IN ACCORDANCE WITH THE CEC PART I.

ACCEPTABLE FOR USE IN ENVIRONMENTAL AIR SPACES OTHER THAN DUCTS OR PLENUMS PER CEC PART I 12-010(3).

MEETS OR EXCEEDS: - CSA 22.2 NO. 203.1

Manufactured "AC90/MC"

Manufactured Manufactured "AC90"



LR 91749

277/480 OR 347/600 Volt 20 Amp

CDN. PATENT - 1219307

U.S. PATENT - 4775802

ITEM	DESCRIPTION	PART#/POSITION	REMARKS	
4	BARE	1	GROUND	
	BLACK/YELLOW TRACER	2	DEDICATED LINE	
	WHITE	3	NEUTRAL	
	RED	4	PHASE A	
	BLACK	5	PHASE B	
	BLUE	6	PHASE C	
	WHITE/YELLOW TRACER	7	DEDICATED NEUTRAL	

## ELECTEC

100-5977 HAZELDEAN ROAD, OTTAWA, ONTARIO, CANADA K2S 1B9 TELEPHONE (613) 836-0300 FAX (613) 836-0391 TOLL-FREE (866) 233-5328 FAX (866) 933-1933 e-mail: support@electeconline.com

## **OWNERSHIP OF DOCUMENTS**

This drawing and accompanying information as instrument of service are the property of **ELECTEC**. Reproduction or use in whole or in part in any form whether the work for which they are presented be executed or not is forbidden without the express written permission of **ELECTEC**.

## JOINER CABLE

w7MFccllld

DRAWN BY:	APPROVED:
J.Y.	D.H.
DATE:	SCALE:
10-DEC-08	N.T.S.

w7MF.9